



INNOVATION. **PRECISION.** EXCELLENCE.



System Specifications

Wetted Components

Valve

- Delrin®
- Teflon®
- Polyethylene

Tank

- Drop in Bottle

Material Line

- UV Safe Teflon®

Maximum Material Pressure

70 PSI

Tank Volume

1 lb (500 g) bottle maximum

Dispense Mode

Manual

Valve Tip

Plastic Luer-Lok™ Adapter

Operating Air Pressure

None

Supply Voltage

None

CAM200-1LB-1

Description of System Operation

1. Bottle of material is placed in pressure pot.
2. Air pressure is applied to material.
3. Lever on either valve is depressed to begin dispense.
4. Fluid pressure is adjusted to control flow.
5. Stroke adjuster on valve can be adjusted for flow rate.

PVA also offers optional accessories for this system:

- Solvent stand to hold valve tip in solvent
- CAM2-SP - Valve spare parts kit
- B62-0653-SP - System spare parts kit

For more information, please contact PVA at info@pva.net or contact your local representative.

Luer-Lok™ is a Becton Dickinson and Co. trademark.
Delrin® and Teflon® are registered trademarks of DuPont.

Headquarters
6 Corporate Drive | Halfmoon, NY 12065
tel +1 518 371 2684 | fx +1 518 371 2688
www.pva.net | info@pva.net