



**WHERE
PRECISION
DRIVES
PRODUCTION**



SYSTEM SPECIFICATIONS

WETTED COMPONENTS:

Valve

- Delrin®
- Teflon®
- Polyethylene

Tank

- Drop in Bottle

Material Line

- UV Safe Teflon®

MAXIMUM MATERIAL PRESSURE:

70 PSI

TANK VOLUME:

1 Pound (500 gm) Bottle Maximum

DISPENSE MODES:

Manual

VALVE TIP:

Plastic Luer-Lok™ Adapter

OPERATING AIR PRESSURE:

None

SUPPLY VOLTAGE:

None

CAM200-1LB-1

Description of System Operation:

1. Bottle of material is placed in pressure pot.
2. Air pressure is applied to material.
3. Lever on valve is depressed to begin dispense.
4. Fluid pressure is adjusted to control flow.
5. Stroke adjuster on valve can be adjusted for flow rate.

For more information on PVA's dispensing capabilities, please contact one of our sales representatives at (518) 371-2684.

PVA also offers optional accessories for this system:

Solvent stand to hold valve tip in solvent
CAM2-SP - Valve spare parts kit
B62-0653-SP - System spare parts kit

One Mustang Drive
Cohoes NY 12047
tel 518 371 2684
fx 518 371 2688
www.pva.net